

485 EX / 485 TX



Wood diameter of up to 24 cm



Feed width 300 mm



Standard weight app. 1,950 kg (EX) and 2,000 kg

☐ **485 EX** with Kubota 55.4 kW (75 hp) **EUR 48.490,-**

☐ **485 TX** with Kubota 55.4 kW (75 hp) **EUR 49.990,-**

Engine and chassis:

Water-cooled, 4-cyl. Kubota turbodiesel engine of 55.4 kW (75 hp). Industrial type freewheel clutch. Single-axle chassis (80 km/h) EX or tandem-axle chassis TX, compl. galvanized. Hitch adjustable in height with inertia brake and ball coupling or DIN towing ring. Front jockey wheel, rear support leg (EX). Walk-on sheet steel fenders. Road lights as per StVZO (shock-protected). Heavy-duty tires 205/65 R17.5 (EX) or 185/70 R14 (TX). TUV expertise and ABE (D, NL, F).

Housing / hopper / chute:

Turning chipping unit (270°). Feed hopper with flap as per CE standards. Pivoting discharge chute with adjustable deflector (conforming to GS standards). Discharge chute on ball bearing flange. Choice of chute lengths (2 sizes). Sound insulation.

Chipping unit:

Chipper with safety circuit as per EN 13525. 2-blade chipping disk with fully adjustable, grindable blades (chip lengths 5-25 mm). Enclosed blade system. Horizontal anvil can be used 4 times; the vertical blade can be used twice. Protection against entangling.

Hydraulic feeding:

Independent hydraulic circuit. PowerGrip feed rollers with hydraulic forced feeding and two separate oil motors. Parallel-guided top roller. Hydraulic chip size adjustment. Level indicator for hydraulic oil tank.

Options

Drive / engine

<input type="checkbox"/> (1)	Power Control System incl. minutes counter	790,-
<input type="checkbox"/> (2)	Main battery switch	195,-
<input type="checkbox"/> (3)	Locking fuel filler cap	49,-
<input type="checkbox"/> (4)	Central lubrication system	595,-

Chassis / Housing

<input type="checkbox"/> (5)	Hydraulic wheel drive (EX only)	3.300,-
<input type="checkbox"/> (6)	Spare tire with support EX	770,-
<input type="checkbox"/> (7)	Spare tire with support TX	310,-
<input type="checkbox"/> (8)	Amber beacon, with support	300,-
<input type="checkbox"/> (9)	Flashing amber beacon, 12 V, with support	420,-
<input type="checkbox"/> (10)	Rear light guards	115,-
<input type="checkbox"/> (11)	Hitch lock for ball coupling or DIN eye coupling	50,-
<input type="checkbox"/> (12)	Additional ball coupling or DIN eye coupling	185,-

Discharge chute

<input type="checkbox"/> (13)	Choice of chute length (standard short/long) without surcharge	
<input type="checkbox"/> (14)	Sound insulation inside chute (-2 dBA)	560,-
<input type="checkbox"/> (15)	Folding discharge chute (standard short/long)	510,-
<input type="checkbox"/> (16)	Horizontal chute extension (up to 1,000 mm)	510,-
<input type="checkbox"/> (17)	Vertical chute extension (up to 500 mm)	510,-

Chipping unit

<input type="checkbox"/> (18)	WhisperCut® chipping system, includes pos. (14)	1.690,-
<input type="checkbox"/> (19)	Palm version for long-fibre material	790,-

Sonstiges

<input type="checkbox"/> (20)	Colour change	150,-
<input type="checkbox"/> (21)	One-day registration charges	220,-
<input type="checkbox"/> (22)	Safety system (SAFEchip)	3.390,-

Total price

EUR*

* excl.VAT – Prices valid as of 01.06.2013

Order no.

Address/Dealer's stamp




schliesing®

www.schliesing.com

Date

Signature



This wood chipper conforms to the safety regulations of DIN EN 13525

- ❑ Turning chipper unit (270°)
- ❑ Folding feed hopper as per CE standard, min. feed depth 1,500 mm
- ❑ Inside hopper dims.: width = 1,170 mm, height = 1,035 mm
- ❑ Chipping disk Ø 800 mm, 40 mm thick
- ❑ Enclosed blade system for a fast, safe and precise blade change
- ❑ Fully adjustable blades (chip sizes 5 - 25 mm)
- ❑ Possibility to sharpen the blades for a long service life (approx. 10x)
- ❑ Horizontal anvil can be used 4 times, the vertical blade twice, ensuring a long service life
- ❑ Top chipping disk protection against entangling at main bearing
- ❑ PowerGrip feed rollers, 300 mm wide, with hydraulic forced feeding via two separate oil motors for an aggressive and uniform feeding of the material, while preventing the branches from lashing to the left and right
- ❑ Parallel-guided top roller for a uniform feeding of the material (no jamming of the fed material)
- ❑ Discharge chute with adjustable deflector fully turning in conformity with GS standards
- ❑ Discharge chute on ball bearing flange
- ❑ Level indicator for hydraulic oil tank
- ❑ Sound insulation of all relevant machine parts (bonnet, in particular)

Our Diesel engines exceed the requirements of emission standards EU 97/68 stage III A

- ❑ Water-cooled, 4-cylinder Kubota turbodiesel engine with 55.4 kW (75 hp)
- ❑ Industrial freewheel clutch, automatically engaging between the engine and the disk
- ❑ Compl. galvanized, corrosion-resistant single-axle chassis (EX) or tandem-axle chassis (TX) for 80 km/h incl. TUV-expertise and ABE (D, NL, F)
- ❑ Fixed, walk-on steel sheet fenders
- ❑ Sturdy front jockey wheel and rear support leg (EX)
- ❑ Hitch adjustable in height with inertia brake and ball coupling or DIN eye coupling
- ❑ Road lights as per StVZO (shock-protected)
- ❑ Heavy-duty tires 205/65 R17.5 (EX) or 185/70 R14 (TX)
- ❑ Total weight:
 - EX (single-axle chassis) ca. 1,950 kg,
 - TX (tandem-axle chassis) ca. 2,000 kg
- ❑ Optional: Power Control System with minutes counter

485 EX / 485 TX

SAFEchip

- ❑ Recommended by BG Gartenbau
- ❑ Noncontacting, electromagnetic protective shield
- ❑ Prevents the user from getting in contact with moving feed roller, thus eliminating the risk of injuries
- ❑ Tested in everyday use
- ❑ Judged positively by the end users
- ❑ Fits seamlessly into the work flow

WhisperCut®

- ❑ Unique, patented system
- ❑ Established on the market for more than 15 years
- ❑ V-shaped blades draw in the wood in a more uniform manner and with less vibrations as compared to conventional knives
- ❑ Increased occupational safety
- ❑ Noise reduction by up to 30%
- ❑ Considerably reduced costs of operation thanks to an increased blade life of 40%
- ❑ Optionally available for nearly all schliesing-Maschinen

schliesing Machinery GmbH

St. Huberter Str. 103
D-47906 Kempen
Tel: +49 (0) 2152 / 9140-0
Fax: +49 (0) 2152 / 9140-50



schliesing®

www.schliesing.com