



Portable Power

# HA 21-30 m<sup>3</sup>/min | Portable Air Compressors



# HA 21-30 m<sup>3</sup>/min | Portable Air Compressors

Model	9/270 HA	9/300 HA	12/235 HA	17/235 HA	21/215 HA
<b>COMPRESSOR</b>					
Free air delivery - m <sup>3</sup> /min (cfm)	27.0 (950)	30.0 (1060)	23.5 (825)	23.5 (825)	21.5 (750)
Rated operating pressure - bar (psi)	8.6 (125)	8.6 (125)	12.0 (175)	17.2 (250)	21.0 (300)
Maximum allowable pressure - bar (psi)	10.3 (150)	10.3 (150)	13.8 (200)	19 (275)	22.8 (330)
Safety valve setting - bar (psi)	15.0 (217)	15.0 (217)	15.0 (217)	28.5 (413)	28.5 (413)
<b>ENGINE</b>					
Make	Cummins	Cummins	Cummins	Cummins	Cummins
Model	QSL9	QSL9	QSL9	QSL9	QSL9
No. of cylinders	6	6	6	6	6
Full load speed - rpm	1800	1800	1800	1800	1800
Power - kW (HP)	224 (300)	254 (340)	224 (300)	254 (340)	254 (340)
Electrical - volts	24	24	24	24	24
Cooling	water	water	water	water	water
Fuel tank capacity - litres	550	550	550	550	550
Air outlets BSPT (British Standard Pipe Thread)	"1 x 2" & 3 x 1¼"	"1 x 2" & 3 x 1¼"	"1 x 2" & 3 x 1¼"	"1 x 2" & 3 x 1¼"	"1 x 2" & 3 x 1¼"
<b>LIMITING AMBIENT TEMPERATURE</b>					
LAT - °C	-10° / +52°	-10° / +52°	-10° / +52°	-10° / +52°	-10° / +52°
<b>TYRES</b>					
Tyre size	750/16 6PR	750/16 6PR	750/16 6PR	750/16 6PR	750/16 6PR
Number of wheels	4	4	4	4	4
<b>DIMENSIONS (WITH RUNNING GEAR)</b>					
Length - mm (tow bar up/down)	4210 / 5339	4210 / 5339	4210 / 5339	4210 / 5339	4210 / 5339
Width - mm	2000	2000	2000	2000	2000
Height - mm	2620	2620	2620	2620	2620
Ground clearance - mm	300	300	300	300	300
Weight (net) - kg	4465	4465	4465	4465	4465
Weight (working) - kg	4925	4925	4925	4925	4925



[www.doosanportablepower.com](http://www.doosanportablepower.com)



**Portable Power**

