

### APPLICATIONS:

The **compact cassette lift DH-C** utilises maximum ease in materials handling without altering the original configuration of the vehicle:

- the platform stows neatly in a **sealed cassette box under the floor** of the vehicle, allowing maximum use of the internal body space, and maintaining full access to the rear doors;
- the DH-C is equipped with a **flat platform** with a thickness of only 15 mm, the low platform height allows the operator to load the platform with minimal effort;
- the DH-C can be fitted to standard factory built panel vans and to the chassis of larger box bodies up to a max. loading floor height of 850 mm;
- the lift is available in 2 variations:  
the **DH-C** is the base version designed for material handling (e.g. for rollcages,...)  
the **DH-CH** is a **passenger lift** equipped with special options for wheelchair handling

### PRINCIPAL CHARACTERISTICS:

- **Flat aluminium platform** with a non slip surface
- **Storage cassette in stainless steel (INOX)**
- Solid arm construction with 2 lift cylinders for maximum lateral stability & reliability
- 12V or 24V hydraulic **power pack premounted** inside the lift frame & **protected by the sealed cassette casing** against road dirt and bad weather conditions
- Electric protection against abuse by unauthorized persons or technical damage in partially or fully retracted position
- Low maintenance bushes fitted to all pivot points
- Tail lift fully functionally tested and pre-assembled before delivery
- **2-button electrical control with spiral cable**
- Controlled without electronic components
- Tail lift fully complies with the CE safety regulations

#### Supplements for the passenger lift DH-CH :



- Hydraulic hand pump
- Safety gates / hand rails fitted to the sides of the platform
- Automatic hydraulic ramp stop at the point of the platform - option [S800]

#### Available as an option on the DH-C and DH-CH :

- [S801] Automatic deployment of the bridge plate to the vehicle loading floor

### TECHNICAL SPECIFICATIONS:

- Platform specifications :  
Useful surface DH-C : ..... 1280 x 800 (D x W)  
Useful surface DH-CH : ..... 1180 x 800 (D x W)  
Platform thickness : ..... 15 mm
- Dimensions of the standard cassette :  
Depth x width : ..... 1100 x 1000 mm  
Height of the cassette : ..... 145 mm
- Max. floor height : ..... 850 mm  
Approx. weight DH-C : ..... 130 kg  
Approx. weight DH-CH : ..... 145 kg



Your dealer: