

Technical Specifications

Model	RF 3120 F
Weight and Dimensions	
Length (m)	3.60
Width (m)	2.24
Height (m)	1.95
Weight (kg)	1840
Bale Chamber	
Rollers (nb) / Slats (nb)	0/30
Diameter (m)	1.20
Width (m)	1.20
Bale ramp	•
Pick-up	
Working width (cm)	170
Number of tine rows	4
Tine spacing (mm)	60
Short crop device	Crop deflector
Pneumatic gauge wheels	•
Intake	
Fork Feeder	•
Driveline	
W-A PTO shaft	o
Shear bolt protection	•
Binding	
Twine (double) / Capacity (m)	•/4
Net / Capacity (m)	o/1
Net & Twine / Capacity (m)	o/1&4
Operations	
Alpha monitor (Electric)	•
Hydraulic outlets	1SA+1DA
Wheels and Axles	
11.5/80-15	•
15.0/55-17	o
19.0/45-17	-
Hydraulic brakes	-
Pneumatic brake	-
Others	
Reversible linkage (up & down)	•
PTO (rpm)	540
Min power requirement (kW/hp)	37/50
• = Standard o = Optional - = Not available	

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations. Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purpose, please contact proper assistance or supervision of a technical assistant. © Kverneland Group Kerteminde AS