

TECHNICAL SPECIFICATION

Applications High Power Tractor
 Description AGRIMAX FORTIS is your reliable partner for all preparation, planting and soil treatment operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads maximizing your business productivity.

Pattern Name AGRIMAX FORTIS

Version STANDARD
 Type TL
 Tire Size 600/70 R 34
 LI/SS 160 D/163 A8

Dimensions (U/M International standard)

Section Width (mm) 591
 Overall Diameter (mm) 1704
 Static Loaded Radius (mm) 761
 Rolling Circumference (mm) 5109
 SRI 800
 Rim Rec DW 18 L
 Rim Alt DW 20 B ; W 18 L



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2160	2520	2835	3150	3465	3735	4140	4500
50	2270	2650	2980	3310	3640	3925	4350	4725
40	2340	2730	3075	3415	3755	4050	4485	4875
30	2485	2900	3265	3625	3985	4300	4765	5175
10 LT	2895	3380	3800	4225	4645	5005	5550	6030
10 HT	2485	2900	3265	3625	3985	4300	4765	5175