

TECHNICAL SPECIFICATION

High Power Tractor Applications

AGRIMAX FORTIS is your reliable partner for all preparation, planting and soil treatment operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads maximizing your business productivity. Description

Pattern Name AGRIMAX FORTIS

STANDARD Version

Туре

Tire Size 650/85 R 38 LI/SS 173 D/176 A8

Dimensions (U/M International strandard)

Section Width (mm) 675 Overall Diameter (mm) 2071 Static Loaded Radius (mm) 935 Rolling Circumference (mm) 6184 SRI 975 Rim Rec DW 23 B

DW 21 B ; DW 20 B Rim Alt

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3120	3640	4095	4550	5005	5395	5980	6500
50	3280	3825	4300	4780	5260	5665	6280	6825
40	3410	3980	4475	4970	5470	5895	6535	7100
30	3590	4190	4710	5235	5760	6205	6880	7475
10 LT	4185	4880	5490	6100	6710	7230	8015	8710
10 HT	3590	4190	4710	5235	5760	6205	6880	7475

