

## TECHNICAL SPECIFICATION

|              |   |
|--------------|---|
| Applications | Tractor / High Power Tractor  |
| Description  | AGRIMAX SIRIO is the high-speed tire (up to 70 km/h - 45 mph) developed by BKT for high-performance tractors. It has been designed to provide best performance both on the road and in the field. The high sidewall flexibility ensures an outstanding comfort to improve the driving experience. |

### Pattern Name **AGRIMAX SIRIO**

|           |             |
|-----------|-------------|
| Version   | HIGH SPEED  |
| Type      | TL          |
| Tire Size | 540/65 R 34 |
| LI/SS     | 152 D/149 E |

#### Dimensions (U/M International standard)

|                            |        |
|----------------------------|--------|
| Section Width (mm)         | 530    |
| Overall Diameter (mm)      | 1566   |
| Static Loaded Radius (mm)  | 721    |
| Rolling Circumference (mm) | 4735   |
| SRI                        | 750    |
| Rim Rec                    | W 16 L |
| Rim Alt                    | W 18   |



#### LOAD CAPACITY TABLE (kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 70         | 1530 | 1755 | 2015 | 2275 | 2535 | 2795 | 3025 | 3250 |
| 65         | 1670 | 1920 | 2205 | 2485 | 2770 | 3055 | 3305 | 3550 |
| 50         | 1755 | 2015 | 2315 | 2615 | 2910 | 3210 | 3470 | 3730 |
| 40         | 1830 | 2105 | 2415 | 2725 | 3035 | 3350 | 3620 | 3890 |
| 25         | 1980 | 2275 | 2615 | 2950 | 3285 | 3625 | 3920 | 4210 |
| 10         | 2505 | 2880 | 3305 | 3730 | 4155 | 4580 | 4955 | 5325 |