

## TECHNICAL SPECIFICATION

Applications	Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
Description	AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

<b>Pattern Name</b>	<b>AS 504</b>
Version	STANDARD
Type	TT
Tire Size	11.0/65 - 12
PR	8

Dimensions (U/M International standard)

Section Width (mm)	273
Overall Diameter (mm)	700
Static Loaded Radius (mm)	321
Rolling Circumference (mm)	2072
Rim Rec	9.00



### LOAD CAPACITY TABLE (kg)

km/h / bar	2.90
10 FR	1650
25 FR	1405
30 FR	1320
40 FR	1180
10 DW	1155
25 DW	980
30 DW	925
40 DW	825

\* Tolerances: Overall Diameter  $\pm 2\%$  | Section Width  $\pm 2\%$  | Rolling Circumference  $\pm 2.5\%$

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..