





CFORCE 450 S/L

Rugged power meets lightweight agility in the CFORCE 450 S/L. With two different sizes (Short and Long), the CFORCE 450 brings nimble versatility to the impressive line of CFORCE ATVs. Loaded with advanced components and premium accessories, the CFORCE 450 S/L open the possibilities for fun and adventure through even the most rugged terrain.









COLORS

Lava Orange

Fire
Red

Danul Inicator

Pearl Injected Black

Truetimber Camo

CFORCE 520 S/L

The CFORCE 520 is equipped with a mid-displacement engine, a 495cc engine. This 34HP engine is an industry leading engine with liquid cooled, single-overhead-cam and fed by a 40mm Bosch Throttle Body. It is featured with optional EPS, choice of single and double seat, and a pure CFMOTO family design DNA.

CFORCE 625/625 TOURING





THE RUGGED BEYOND

Inside our hearts lies an intrinsic yearning for freedom, a desire to pursue the rugged beyond. Maybe the best thing about hunting, fishing, camping or even working is just getting there, especially when you saddle on an all-new CFORCE. The CFORCE 625 highlights the full lineup of versatile ATVs. With next-generation chassis and styling, this exciting machine is getting plenty of attention. The all-new 625 comes in either a one or two-up version.











CFORCE 850 XC

Features both outstanding performance and versatility. Configured with powerful and responsive hardcore engine, it is sure to provide you with great riding experience and also rich in accessories engineered to maximize the riding fun.





COLORS

Athens Blue



Lava Orange

Blue







CFORCE 1000

Has more power than any other members in CFMOTO ATV family. Deploying a purpose built liquid-cooled engine, it is a great combination of performance, functionality and aesthetics. CFMOTO is always progressive to push the limits further higher to give you unrivalled riding experience.



UFORCE 800

UFORCE 800 has all the power and maneuverability to tackle any size project anywhere. As a utility member in the CFMOTO vehicle family, it will always come with the essentials: exceptional performance, high-precision handing and maximum riding pleasure with optimum user value. Go ahead and pick out your UFORCE 800. Lead the charge. It won't be long before you, and everybody else, realize you made a smart move.













UFORCE 1000

The new comer UFORCE 1000 is definitely the all-round winner in the CFMOTO utility range with reasonable ergonomics, outstanding design, potent power and excellent handling performance. The on-demand 2W/4W switch and other integrated technologies further improve its utility features. The UFORCE 1000 will help you tackle problems while assuring you of a sporty, comfortable, safe and pleasing ride.





ZFORCE 550 EX

The streamlined design, low center of gravity and superb trafficability make it become the speed dominator from desert to open field, which shows out a very sporty SSV vehicle in front of us.



ZFORCE 1000

With the launch of ZFORCE 1000, CFMOTO Side-by-Side family stepped into a new level. Based on the mature chassis platform of SSV family, the new roaring engine machine is going to bring you to experience wonderful off-road riding, no matter in what road conditions. The ZFORCE 1000 is equipped with the top configurations in the industry, excellent handling, and perfect ergonomics design, all those will no doubt contribute to the unbelievable riding pleasure.





EXPLORE NEW HORIZONS

If you're looking for high adventure, look no further than ZFORCE. The ZFORCE lineup of performance side by sides, including the stunning all-new 1000 Sport, are built to handle your next off-road extravaganza. This machine doesn't just come with bells and whistles, but a full band. Nothing has been spared in delivering performance and comfort, so you can enjoy the exhilaration of riding and taking in the great outdoors. Your next adventure story is out there. Get out and capture it.



ZFORCE 1000 SPORT











CFORCE 450 S/450 L



CFORCE 520 S/520 L



CFORCE 625/625 TOURING



CFORCE 850 XC



CFORCE





UFORCE



ZFORCE 550 EX



ZFORCE



ZFORCE



	S
	Z
Į	0
\$	S
监	Z
5	ш
O	Σ
	$\overline{}$

ı	ш
	Z
ō	5
	Z
ı	ш

<u>ഗ</u>
SS
¥
כ

-	Length x Width x Height	S: 2180×1100×1150 mm L: 2380×1100×1350 mm	S: 2180×1100×1150 mm L: 2380×1100×1350 mm	2035×1180×1220 mm T: 2235×1180×1390 mm	2395×1264×1420 mm	2395×1264×1420 mm
	Wheelbase	S: 1260 mm L: 1460 mm	S: 1260 mm L: 1460 mm	1280 mm T: 1480 mm	1480 mm	1480 mm
	Seat Height	530 mm	530 mm	530 mm	585 mm	585 mm
	Minimum Ground Clearance	250 mm	250 mm	270 mm	285 mm	300 mm
	Minimum Turning Diameter	S: 7.5±0.5 m L: 8.5±0.5 m	S: 7.5±0.5 m L: 8.5±0.5 m	7.25 m T: 7.4 m	7.8 m	7.8 m
	Curb Weight	S: 358 kg L: 382 kg	S: 358 kg L: 382 kg	395 kg T: 400 kg	480 kg	490 kg
	Payload Capacity	230 kg	230 kg	230 kg	240 kg (Including driver)	240 kg (Including driver)
	Fuel Capacity	14 L	14 L	18 L	30±1 L	30±1 L
	Engine Type	Single cylinder,Liquid cooled, 4-stroke,SOHC,4-Valve	Single cylinder,Liquid cooled, 4-stroke,SOHC,4-Valve	Single cylinder,Liquid cooled, 4-stroke,SOHC,4-Valve	V-Twin cylinder,Liquid cooled, 4-stroke,SOHC,8-Valve	V-Twin cylinder, Liquid cooled, 4-stroke,SOHC,8-Valve
	Displacement	400 cc	495 cc	580 cc	800 cc	963 cc
	Transmission	CVT	CVT	CVT	CVT	CVT
	Drive	Switchable 2WD/4WD	Switchable 2WD/4WD	Switchable 2WD/4WD	Switchable 2WD/4WD	Switchable 2WD/4WD
	Brake	Front wheel side brake + rear wheel central axle brake + central axle parking	Front wheel side brake + rear wheel central axle brake + central axle parking	Four-wheel side brake (CBS) + rear wheel sideparking	Four-wheel side brake (CBS) + rear wheel sideparking	Four-wheel side brake (CBS) + rear wheel sideparking
-	Suspension	Front/Rear: Double arm independent suspension	Front/Rear: Double arm independent suspension	Front/Rear: Double A-arm independent suspension	Front: Double A-arm, independent suspension Rear: Trailing arm, independent suspension	Front: Double A-arm, independent suspension Rear: Trailing arm, independent suspension
	Shock Absorber	Front/Rear: Spiral spring oil shock absorber	Front/Rear: Spiral spring oil shock absorber	Front/Rear: Coil spring + oil damping	Front/Rear: Coil spring + oil damping (optional coil spring + air damping)	Front/Rear: Coil spring + air damping
	Wheels	Front: 12×6.0 AT Rear: 12×7.5 AT	Front: 12×6.0 AT Rear: 12×7.5 AT	Front: 12×6.0 AT Rear: 12×7.5 AT	Front: 14×7.0 AT Rear: 14×8.0 AT	Front: 14×7.0 AT Rear: 14×8.0 AT
	Tires	Front: AT 25×8.00-12 Rear: AT 25×10.00-12	Front: AT 25×8.00-12 Rear: AT 25×10.00-12	Front: 25×8.0-12 Rear: 25×10.0-12	Front: 26×9.00-14 / 26×8.00-14 Rear: 26×11.00-14 / 26×10.00-14	Front: 27×9.00R14 Rear: 27×11.00R14
	Color(s) Available	Pearl Injected Blue Pearl Injected Black Lava Orange Truetimber Camo	Fire Red Pearl Injected Black Lava Orange Truetimber Camo	Pearl Injected Blue Lava Orange Titanium Grey Truetimber Camo	Lava Orange Athens Blue Titanium Grey Truetimber Camo	Lava Orange Athens Blue Ghost Grey Truetimber Camo

UFORCE
800
2922×1488×1864 mm

2922×1488×1864 mm	2945×1615×1850 mm	
1830 mm	2050 mm	
445 mm	500 mm	
258 mm	280 mm	
9.5 m	8.2 m	
625kg (Oil filled)	765 kg	_

0070 1510 1070		
2870×1510×1830 mm	3140×1510×1845 mm	3135×1820×1820 mm
2040 mm	2040 mm	2285 mm
395 mm	395 mm	395 mm
305 mm	310 mm	310 mm
9.5 m	9.5 m	11 m
580 kg	620 kg	690 kg
295 kg	310 kg	350 kg
27 L	27 L	36.5 L
Single cylinder, Liquid cooled, 4-stroke, SOHC, 4-Valve	V-Twin cylinder Liquid cooled 4-stroke, SOHC, 8-valve	V-Twin cylinder, Liquid cooled, 4-stroke, SOHC, 8-Valve
495 cc	963 cc	962.6 cc
CVT	CVT	CVT
Switchable 2WD/4WD	Switchable 2WD/4WD	Switchable 2WD/4WD
Four-wheel side brake (CBS) + rear wheel side parking	Four-wheel side brake (CBS) + rear wheel side parking	Four-wheel side brake (CBS) + rear wheel side parking
Front/Rear: Double arm, independent suspension	Front/Rear: Double arm, independent suspension	Front: Double A-arm,independent suspension Rear: Multi-connectingrods, independent suspe
Front/Rear: Coil spring + air damping	Front/Rear: Coil spring + air damping	Front/Rear: Coil spring + air damping