



www.dandah.com

D&A HEAVY INDUSTRIES BACKHOE LOADER AND SKID STEERS LOADER

Easy to operate and Most suitable
For Backhoe Loader, Excavator,
Skid-Steer and Mini-Excavator



■ Specification

MODEL		D&A 40V	D&A 50V	D&A 60V	D&A 70V	D&A 80V
Operating Weight	kg(lbs)	260(572)	310(682)	330(728)	480(1,058)	540(1,191)
Blow Rate	bpm	380~1,000	380~1,000	380~900	400~1,000	400~1,000
Required Oil Flow	lpm(gpm)	35~70(9.24~18.48)	35~70(9.24~18.48)	40~80(10.16~20.32)	45~90(11.88~23.76)	50~100(13.2~26.4)
Operating Pressure	kg/(=psi)	110~165(1,595~2,393)	110~165(1,595~2,393)	120~165(1,740~2,393)	140~160(1,998~2,272)	140~160(1,998~2,272)
Overall Length	mm(inch)	1,396(54.96)	1,597(62.9)	1,639(64.53)	1,894(74.6)	2,062(81.2)
Hammer Tool	mm(inch)	70(2.75)	70(2.75)	75(2.95)	80(3.14)	90(3.54)
Suitable Carrier	ton(lbs)	3.0~6.5(6,600~14,300)	3.0~6.5(6,600~14,300)	4.5~8.0(9,900~17,600)	4.5~8.0(9,900~17,600)	6.0~10.0(13,200~22,000)

* Above specifications are subject to change without notice.



■ Specification

MODEL		D&A 30V	D&A 50V	D&A 60V
Operating Weight	kg(lbs)	335(737)	380(836)	400(880)
Blow Rate	bpm	550~1,100	380~1,000	380~900
Required Oil Flow	lpm(gpm)	30~60(7.92~15.84)	35~70(9.24~18.48)	50~80(13.2~20.32)
Operating Pressure	kg/(=psi)	110~165(1,595~2,393)	110~165(1,595~2,393)	120~165(1,740~2,393)
Overall Length	mm(inch)	1,530(60.2)	1,615(63.6)	1,639(64.53)
Hammer Tool	mm(inch)	70(2.75)	70(2.75)	75(2.95)
Suitable Carrier	ton(lbs)	2.0~4.5(4,400~9,900)	3.0~6.5(6,600~14,300)	4.5~8.0(9,900~17,600)

* Above specifications are subject to change without notice.

