


MF 345 Xtra

2WD, Simple yet powerful machinery



Key Features

- Fuel efficient, high performance 3 cyl. engine
- Straightforward 8 x 2 mechanical transmission
- Live single speed PTO
- Opening bonnet for easy maintenance
- Frame and sun canopy
- Front weights
- Drawbar
- Trailer tipping pipe

MF Dealer Support

Exclusively available from your accredited MF Dealer:

- 12 month manufacturer's warranty
- Genuine AGCO parts
- Professional aftersales service
- Factory-approved technicians



Specifications

		MF 345 Xtra
Engine Performance		
Engine hp power - * Certified to BS AU 141a : (1971)	@ 2250rpm	50 hp
Max torque	@ 1400rpm	172 Nm
PTO power at rated engine speed		44 hp**
Engine		
Engine type/no. of Cylinders/Capacity/Aspiration		Diesel 3.152 / 3 / 2.5 / Natural
Throttle control		Hand and foot
Exhaust		Vertical
Clutch		Dual
Transmission		
Туре		Sliding Spur 8 forward, 2 reverse road speed 30kph at 2250 engine rpm with 12.4/11-28 rear tyres
Power Take-off		
Live single speed - 540 rpm		1,789 rpm
Shaft diameter/Number of splines	r	35mm / 6
Hydraulics		
Functions		Draft control, Position control. Response control, Constant pumping
Oil flow	litres/min	16
System pressure	Мра	19.2
Lift capacity at lower link ends	kg	1,415
3-point linkage		Cat 1 & 2 interchangeable balls
Brakes		
Brake type		Out board drum brakes
Actuation		Mechanical, Independent or locked together
Parking brake		Hand lever operated
Differential lock		Mechanical
Tyres		
Front		6.00 - 16 (6PR) Pressed wheels
Rear		12.4 / 11 - 28 (6PR) Pressed wheels
Instrumentation		
Gauges	Tachometer, hourmeter, fuel level, battery condition & water temperature	
Warning lights	Direction indicators, battery charge, headlight main beam, low engine oil pressure, brake lights & auxiliary socket	

engine oil pressure, brake lights & auxiliary socket

	MF 345 Xtra	
Weights and Dimensions*		(with 6.00-16 front & 12.4/11-28 rear wheels
Gross weight	kg	1,995***
Wheelbase	mm	1,930
Overall length - (links horizontal)	mm	3,454
Overall width (min)	mm	1,676
Overall height over exhaust	mm	2,134
Overall height over steering wheel	mm	1,448
Capacities		
Fuel tank	litres	47.5
Engine sump	litres	6.8
Cooling system	litres	10.2
Hydraulic system	litres	33
Steering box	litres	0.9
Oil bath air-cleaner	litres	0.65
Turning circle		
With brakes	mm	5,560
Without brakes	mm	6,200
Ground clearance		
Under gearbox	mm	338
Front axle		
Туре		Box section, adjustable
Track Adjustment		
Front	mm	1,245 - 1,854
Rear	mm	1,219 - 1,930
Steering		
Туре		Manual

Standard equipment

Frame and sun canopy, Shell fenders, Stabiliser chains, Weight frame with front weights (6 x 25kg), Standard tool box, Adjustable top link, Top link end Cat I & II balls, Spring suspension seat, Operator manual, Swinging drawbar & Trailer tipping pipe.



For even greater productivity a range of optional equipment is available, For full details please consult your local Massey Ferguson dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

^{*} Approximately ** Manufacturer's estimate *** Gross weight includes front weights, frame, sun canopy and swinging drawbar.