

Tandem Vibratory Roller

SWC203

WWW.SINOWAY.SH

WWW.SINOW

WWW.SINOWA



W.SINOWAY.SH.COM

Model	Changchai ZN385Q
Type	Three-cylinder, water-cooled
nor	mally aspirated, mechanical injection
Rated power	21KW
Rated speed	2400rpm

Operating weight	3000Kg
Type Hydraulic single dru	um vibration
Frequency	50Hz
Amplitude	0.5mm
Static linear load12	28/172N/cm
Vertical oscillation	80
Drum shell thickness	12mm
Centrifugal force	- 30KNI~2

Overall length	2900mm
Overall width	1314mm
Overall height	2600mm
Drum width	1000mm
Wheel base	- 2100mm
Drum Dia	700mm
Ground clearance	220mm

Type Mech	าan <mark>ical d</mark> rive(Gear box)
Grade ability	20%
Gear shifts(Forward/Reve	erse) F2/R2
Travelling speed (km/h)	
Forward/Reverse I	
Forward/Reverse II	

Type Hydraulic articulated steer	ing
Steering cylinder Two cylind	ers
Steering pump Gear pu	mp

Fuel tank	1	 -	-	-	 	 -	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		70L
Water tank		 _	_	_	 	 L	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	-	1001

Axle

Drive type	Re	ear whe	el drive
Front axle load			1280Kg
Rear axle load			1720Kg

Braking System

Service brakeBand brak	е
Parking brake Ratchet brak	е