

Technical specifications

PL 1761



(Perfectly fitting front linkages or 3-point point hitch, fork-lift, construction equipment,...)

Series

Overall width	2000 mm
Operating width	1700 mm
Blade height - centre	750 mm
Blade height - side	860 mm
weight	345s kg

UNI-200

Standard equipment

1 blade with safety release facility
Depth skids
Mechanical swivel device 30°
Steel wear bar 150 x 15 mm, screwed
Signal flags

Accessories

Hydraulic swivel device 30°	PL 1783
Wheels, diam. 200 mm, <i>when ordered with blade</i>	PL 1555
Wheels, diam. 200 mm, <i>separate delivery</i>	PL 1556
Hydraulic pivoting device	PL 1786

Adaptor for snow blade - series Universal

Adaptor for 3-point front linkage, cat. 2	PL 1775
Adaptor for 3-point rear linkage, cat.1 and cat.2	PL 1776
Adaptor for front-end loader Eurokipp with quick-change plate (<i>incl. pivoted compensation</i>)	PL 1777
Adaptor for front-end loader Ökonom and Universal	PL 1778
Adaptor for self-assembly to third-party front-end loaders (<i>straight traverse, width approx. 1,20m</i>)	PL 1779
Adaptor for forklift	PL 1780
Adaptor for quick coupling triangle (Weiste-triangle)	PL 1781
Adaptor for construction machinery (JCB, etc.)	PL 1782

