



# WB05



Typ	Model	Type	WB05
Maschinengewicht(kg)	Machine weight (kg)	Poids en marche(kg)	310
Max. Ladekapazität(kg)	Max. loading capacity(kg)	Poids utile max.(kg)	500
Ladevolumen(m <sup>3</sup> )	Deck body capacity(m <sup>3</sup> )	Capacité de benne(m <sup>3</sup> )	0,21
Getriebe	Transmission	Transmission	Mechanical
Fahrgeschwindigkeit Vorwärts	Travelling speed Speed forward	No Vitesses Vitesses en avant	1 2.5 km/h 2 4.5 km/h
Rückwärts	Speed reverse	Vitesses en arrière	1 2.2 km/h 2 4.0 km/h
Motor Typ	Engine Type	Moteur Modèle	Air cooled Gasoline MITSUBISHI GM182L
Anyahl Zylinder	No. of cylinder	No Cylindre	1
Max. Leistung(PS)	Max.output(PS)	Puissance max.(PS)	6,0
Starteinrichtung	Starting method	Démarrreur	Recoil
Hauptabmessungen(mm)	Machine dimensions(mm)	Dimensions(mm)	
Gesamtlänge	Overall length	Longueur hors tout	1.800
Gesamtbreite	Overall width	Largeur hors tout	720
Gesamthöhe	Overall height	Hauteur hors tout	1.050
Bodenfreiheit	Ground clearance	Grade au sol	110
Kettenabstand mitting	Crawler center distance	Distance des chenilles des cotés intérieur	520
Kettenabstand außen	Crawler outside distance	Distance des chenilles des cotés extérieur	720
Muldenabmessungen(mm)	Deck body dimensions(mm)	Dimensions de la benne	
Gesamtlänge	Overall length	Longueur hors tout	1.130
Gesamtbreite	Overall width	Largeur hors tout	650
Gesamthöhe	Overall height	Hauteurs hors tout	350
Unterwagen(mm)	Under carriage(mm)	Chassis(mm)	
Bodenberührungslänge	Ground contact length	Longueur sur sol	825
Kettenbreite	Crawler width	Largeur des chenilles	200
Steigfähigkeit(Grad)	Gradeability(deg.)	Rampe franchissable à vide(deg.)	
Abladen	Unload	à vide	25
Laden	Load	en charge	20
Kippsystem	Dumping type	Système de basculement	Hydraulic
Hydr. Kipprichtung	Dumping direction	Direction de basculement	Vowärts/Forward/En avant
Hydraulikpumpe	Hydraulic pump	Pompe hydraulic	
Druck(kgf/cm <sup>2</sup> )	Pressure(kgf/cm <sup>2</sup> )	Pression(kgf/cm <sup>2</sup> )	70
Durchflußmenge(Ca.)	Discharge volume	Charge utile(apprx.)	8.0/1800(L./Min.)
Lenkbremse	Steering brakes	Frein de direction	Zahn/Tooth/Dents



**Yuasa Trading Deutschland GmbH**

Tel: +49 (0)6152-9778-0 Fax: +49(0)6152-9778-15 e-mail: info@yuasa-europe.com

**Yuasa Trading France**

Tel: +33(0)1 69 43 31 31 Fax: +33(0)1 69 43 46 30 e-mail@j.p.milhaud@yuasa-europe.com